

Vertical-Insert 24-Pin Passbook Printer



BP-900KII

Vertical-Insert 24-Pin Passbook Printer

Highlights:

- Fast printing speed of up to 400 characters per second
- Better connectivity with Standard Parallel Interfaces
- Optimum efficiency with 7-pay forms printout (Original + 6 Copies)
- Trustworthy print head (500 million strokes)
- Built-in emulation of EPSON ESC/PK2, OKI5530SC
- Maximum paper thickness of up to 2.8mm

BP-900KII

Vertical-Insert 24-Pin Passbook Printer



Jolimark BP-900KII

Specification:

Print type	24-pin impact dot matrix
Print direction	Bi-directional with logic seeking
Print width	70 ~ 250 mm
Print speed	Normal: 120CPS High speed: 360CPS Super high speed: 400CPS
Print head	500 million strokes/wire
Character sets	17 international character sets U.S.A, France, Germany, U.K, Denmark1, Sweden, Italy, Spain1, Japan, Norway, Denmark2, Spain2, Latin Am, Korea, Legal, Netherlands, Turkey
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, OCR-A, OCR-B, ORATOR
Bar code	EAN 8/13, NW7, Code 39, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, Code 128B/C
Character pitch	10CPI, 12CPI, 15CPI, proportional
Line space	1/6 inch, 1/8 inch, programmable in 1/360 inch increments
Emulation	EPSON ESC/PK2, IBM, OKI5530SC, Olivetti PR40/PR50/PR2
Interface	
Standard	Bi-directional parallel interface (IEEE-1284 Nibble mode), USB 2.0 (Full- Speed) interface
Options	10/100Base-T Ethernet interface, RS-232C serial interface
Input Buffer	132KB
Ribbon	
Color	Black
Life	> Life:6 million characters(draft mode)

Jolimark BP-900KII handles thick booklet of up to 2.8mm. With 2 independent paper handlers, it can print on vertically bound booklet which has different thickness on each page. Together with enhanced features such as automatic sheet alignment and automatic print head adjustment, it handles high volumes of passbooks, tickets and other documents with easy.

Noise	Print noise level, Operating ≤52dB (A) , Silent mode ≤50dB (A)
Paper feed type	Single paper, Passbook,: front in, front out/ front in, rear out;
Paper specification	
Single paper	Width: 70 ~ 250 mm, Length: 67 ~ 300 mm
Continuous paper	Width: 75—245mm, Length: 66—536mm
Passbook	Width: 100 ~ 250 mm, Length: 75 ~ 180 mm
Max paper thickness	2.8mm
Passbook thickness	2.3mm after opening
Vertically Bound Booklet	1.5mm thickness difference between left and right after opening
Copy capability	Original+6 copies
Automatic function	Automatic gap adjustment Automatic document alignment Automatic paper edge detection Arbitrarily paper feeding
Special function	Automatic Pin Break Compensation Automatic Pin Alternation
Dimension	397mm (W) ×287.5mm (D) ×195mm (H)
Weight	Approx. 8.3 Kg
Environmental conditions	
Operating	Temperature 5 ~ 40°C Humidity 20%RH ~ 80%RH (No condensation)
Storage	Temperature: -40~55°C, Humidity: 10%RH ~ 90%RH (No condensation)
Power requirements	Rated voltage: 90-264V Rated frequency range: 50Hz/60Hz

Certificate



DNVISO14001



BSIISO9001



OHSAS 18001

*The specifications above are subject to be changed without notice.

kabim®
Ofis Teknolojileri