

Para		Mode	YT-6000		
Picture					
Picture					
Performance Parameter					
Depth Filed			Tested Code	Minimum	Maximum
			5mil code39	1CM	9CM
			13mil EAN13	1CM	21CM
			12mil DM	1CM	19CM
			16mil QR	1CM	25CM
			7MIL PDF417	1CM	11CM
Lamp-house Type			White LED		
Indicator light			Red&Blue LED, red light mains tips, blue light decoding flicker tips		
Buzzer			Start Tips, Decoding success tips		
Button			Switch scanning mode		
Scan Pattern			Automatic induction continuous scan,Automatic induction single scan		
Keyboard support			Support multiple languages		
Decode Accuracy			Code 39 4mil		
Code Available			1D, 2D Codes printing on Paper or film or Cellphone screen		
Scanning Speed			2300 Times/Second		
Secondary development			Not support		
Barcode output editing			Not support adding prefix and suffixes		
Minimum Contrast			20%		
Barcode Types			EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codebar, industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI. 2D PDF417、MICROPDF417、Datamxtrix、QR、Maxicode、Aztec、etc		
System Compability			Linux, Android, Windows XP, Windows VISTA, Windows 7, Windows 8, Windows 10, Windows Server 2003, Windows Server 2008, Windows Server 2010		
Barcode Sensit	Horizontal :		72°		
	Vertical:		82°		
	Rotated:		360°		
Mechanical and Electric Performance					
SIZE(Length x Width x Height)			124mm*110mm*160mm		
Communication			USB, Serial port		
Data line length			180CM(±3cm)		
Net Weight			445g		
Max.Power			415MA		
Current	Standby current		370MA		
	Working Current		385MA		
Environmental Parameter					
Conserve Temperature			~20℃ ~60℃		
Working Temperature			~20℃ ~55℃		
Working Humidity			5-95% Non-Condensed		
Height range			1.5M		
IP Rating			IP54		