

SPECIFICATIONS

Model	iQ200
Printing Method	Direct Thermal
Printing Resolution	203 dpi
Max Printing Speed	5 ips (127 mm/s)
Max Printing Width	4.09" (104 mm)
Max Printing Length	40" (1016 mm)
Memory	8 MB FLASH ROM, 16 MB SDRAM
Media	Width: 4.72" (120 mm) max., 0.98" (25 mm) min. Supply roll: OD 5" (127 mm) max., or OD 9" (228.6 mm) max. (using External Media Stand); ID 1" (25.4mm) min. Thickness: 0.003" - 0.006" (0.08 - 0.15 mm), including liner.
Media Sensor	Reflective (multiple mounting positions) / Transmissive (Adjustable)
Fonts	Five built-in ASCII fonts, Downloadable TrueType fonts
Bar Code Types	1D Barcode: Code 39, Code 93, Code 128/subset A,B,C, Codabar, Interleave 2 of 5, UPC A/E 2 and 5 add-on, EAN-13/8/128, UCC-128, etc. 2D Barcode: MaxiCode, PDF417, Data matrix, QR Code, etc.
Interfaces	USB DEVICE 2.0, RS-232 Serial
Power Rating	24 VDC Power adapter
Weight	1.8 kgs
Dimensions	W 8.3" (210 mm) x D 10" (255 mm) x H 5.9" (150 mm)
Operating Environment	Temperature: 32°F ~ +104°F (0°C ~ 40°C), Relative humidity: 5% ~ 85% non condensing
Storage Environment	Temperature: -40°F ~ +140°F (-40°C ~ 60°C), Relative humidity: 5% ~ 85% non condensing
Accessories	Standard Item: External Media Stand; Optional Items: External Label Rewinder, Guillotine Cutter, Media Guide Adaptor, Wi-Fi

* All specifications are subject to change without notice.

APPLICATIONS

- Courier Service
- Logistic Department
- eBay Seller
- E-Commerce Platform
- Restaurant
- Healthcare

...



SAMPLES



POSTEK
POSTEK ELECTRONICS CO., LTD.

kabim®
Ofis Teknolojileri