

3 inch Mobile Printer

MP-B30

Measuring
InstrumentPDA/
Smart Device

Barcode

Portable
PrinterMedical
Equipment

- Compact & Light Weight
- Drop rating: 1.8m (6feet), IP rating: IP54
- Printing Speed: 127mm/sec max
- Simple Operation & Stylish Design
- Option Cradle for Charging



MP-B30



Model		MP-B30
Printing	Method	Thermal line dot printing
	Number of dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	80 ⁺⁰ ₋₁
	Printing width (mm)	72
	Printing speed (mm/sec) max	127 (5inch)
	Outside diameter of paper roll (mm)max	Φ51
	Character matrix (HxW dots)	24 × 12, 24 × 24, 16 × 8, 16 × 16
Type of paper	Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
	Type of paper	Roll paper
Character type	Code page (17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character	
Barcode	UPC-A/E, JAN (EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar	
Power supply	Li-Ion Battery	
Communication interface	USB, Bluetooth®, W-LAN ^{*1}	
Input buffer	4K bytes	
Command	ESC/POS™ conformity	
Cutting method	Tear bar	
Falling resistance	1.8m ^{*2}	
IP rating	IP54 ^{*2}	
Operating Temperature (°C)	-20 to 55	
Service life: Abrasion resistance (km)	50 ^{*3}	
Dimensions (W×D×Hmm)	105 x 126 x 58 ^{*4}	
Mass (g)	395 ^{*5}	
Standard	FCC, CE, VCCI	
Bundled item	AC adapter, Battery, USB cable, Belt clip	
Option	Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap	
SW	Printer driver, OPOS, POS for .NET, Windows® CE (SDK), Android™ (SDK), iOS (SDK)	

*1 Selected model. *2 This number is test result based on SII procedures, not guaranteed value. *3 Use recommended thermal papers. *4 Excluding protrusion *5 with battery, without paper roll

kabim[®]
Ofis Teknolojileri